




FOR 0,35M SPACING CONSULT PAGE 137



PRODUCES DROPLETS
COARSE TO
ULTRA COARSE

ACCORDING TO WORKING PRESSURE

OPENING ANGLE



60°

FLAT FAN



AIR INDUCTION



30 - 110 PSI
2,07 - 7,58 bar
207 - 758 kPa

- High durability ceramic nozzle (99% alumina) with outstanding wear-resistance.
- Excellent flow rate precision (ISO 10625:2018).
- Produces 60° offset flat fan spray pattern.
- The ceramic orifice ensures good standardization and droplet distribution on the target.
- Good for directed spraying and hose drip application.
- Venturi system with air induction produces large air-filled droplets with micro-bubbles.
 - Low risk of potential drift.
- Used at the end of the spray boom around the perimeter of the field to protect sensitive crops.

FOR MORE
INFORMATION



CODE NOZZLE	DROPS SIZE	BAR	PSI	kPa	L/min	LITERS PER HECTARE													
						4	5	6	7	8	9	10	12	14	16	18	20	25	
						km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	
MJ192/1 PB-IA 01	UC	2,07	30	207	0,33	100	80	66	57	50	44	40	33	28	25	22	20	16	
	EC	2,76	40	276	0,38	115	92	77	67	58	51	46	38	33	29	26	23	18	
	EC	3,45	50	345	0,43	129	103	86	74	64	57	51	43	37	32	29	26	21	
	EC	4,14	60	414	0,47	141	113	94	81	70	63	56	47	40	35	31	28	23	
	EC	4,83	70	483	0,51	152	122	101	87	76	68	61	51	43	38	34	30	24	
	VC	5,52	80	552	0,54	163	130	108	93	81	72	65	54	46	41	36	33	26	
	VC	6,21	90	621	0,58	173	138	115	99	86	77	69	58	49	43	38	35	28	
	VC	6,89	100	690	0,61	182	146	121	104	91	81	73	61	52	45	40	36	29	
MESH 100	C	7,58	110	758	0,64	191	153	127	109	95	85	76	64	55	48	42	38	31	
MJ193/1 PB-IA 015	UC	2,07	30	207	0,50	149	120	100	85	75	66	60	50	43	37	33	30	24	
	EC	2,76	40	276	0,58	173	138	115	99	86	77	69	58	49	43	38	35	28	
	EC	3,45	50	345	0,64	193	154	129	110	96	86	77	64	55	48	43	39	31	
	EC	4,14	60	414	0,70	211	169	141	121	106	94	85	70	60	53	47	42	34	
	VC	4,83	70	483	0,76	228	183	152	130	114	101	91	76	65	57	51	46	37	
	VC	5,52	80	552	0,81	244	195	163	139	122	108	98	81	70	61	54	49	39	
	VC	6,21	90	621	0,86	259	207	173	148	129	115	104	86	74	65	58	52	41	
	C	6,89	100	690	0,91	273	218	182	156	136	121	109	91	78	68	61	55	44	
MESH 100	C	7,58	110	758	0,95	286	229	191	164	143	127	114	95	82	72	64	57	46	
MJ194/1 PB-IA 02	UC	2,07	30	207	0,66	199	159	133	114	100	89	80	66	57	50	44	40	32	
	EC	2,76	40	276	0,77	230	184	153	131	115	102	92	77	66	58	51	46	37	
	EC	3,45	50	345	0,86	257	206	172	147	129	114	103	86	74	64	57	51	41	
	EC	4,14	60	414	0,94	282	225	188	161	141	125	113	94	81	70	63	56	45	
	VC	4,83	70	483	1,01	304	244	203	174	152	135	122	101	87	76	68	61	49	
	VC	5,52	80	552	1,08	325	260	217	186	163	145	130	108	93	81	72	65	52	
	VC	6,21	90	621	1,15	345	276	230	197	173	153	138	115	99	86	77	69	55	
	C	6,89	100	690	1,21	364	291	243	208	182	162	146	121	104	91	81	73	58	
MESH 50	C	7,58	110	758	1,27	382	305	254	218	191	170	153	127	109	95	85	76	61	
MJ194/2 PB-IA 025	VC	2,07	30	207	0,83	249	199	166	142	125	111	100	83	71	62	55	50	40	
	VC	2,76	40	276	0,96	288	230	192	164	144	128	115	96	82	72	64	58	46	
	EC	3,45	50	345	1,07	322	257	214	184	161	143	129	107	92	80	71	64	51	
	EC	4,14	60	414	1,17	352	282	235	201	176	157	141	117	101	88	78	70	56	
	EC	4,83	70	483	1,27	381	304	254	217	190	169	152	127	109	95	85	76	61	
	EC	5,52	80	552	1,36	407	325	271	232	203	181	163	136	116	102	90	81	65	
	VC	6,21	90	621	1,44	431	345	288	247	216	192	173	144	123	108	96	86	69	
	VC	6,89	100	690	1,52	455	364	303	260	227	202	182	152	130	114	101	91	73	
MESH 50	VC	7,58	110	758	1,59	477	382	318	273	239	212	191	159	136	119	106	95	76	
MJ195/1 PB-IA 03	UC	2,07	30	207	1,00	299	239	199	171	149	133	120	100	85	75	66	60	48	
	EC	2,76	40	276	1,15	345	276	230	197	173	153	138	115	99	86	77	69	55	
	EC	3,45	50	345	1,29	386	309	257	221	193	172	154	129	110	96	86	77	62	
	EC	4,14	60	414	1,41	423	338	282	242	211	188	169	141	121	106	94	85	68	
	VC	4,83	70	483	1,52	457	365	304	261	228	203	183	152	130	114	101	91	73	
	VC	5,52	80	552	1,63	488	391	325	279	244	217	195	163	139	122	108	98	78	
	VC	6,21	90	621	1,73	518	414	345	296	259	230	207	173	148	129	115	104	83	
	VC	6,89	100	690	1,82	546	437	364	312	273	243	218	182	156	136	121	109	87	
MESH 50	C	7,58	110	758	1,91	572	458	382	327	286	254	229	191	164	143	127	114	92	
MJ195/2 PB-IA 04	UC	2,07	30	207	1,33	399	319	266	228	199	177	159	133	114	100	89	80	64	
	UC	2,76	40	276	1,53	460	368	307	263	230	205	184	153	131	115	102	92	74	
	EC	3,45	50	345	1,72	515	412	343	294	257	229	206	172	147	129	114	103	82	
	EC	4,14	60	414	1,88	564	451	376	322	282	251	225	188	161	141	125	113	90	
	EC	4,83	70	483	2,03	609	487	406	348	304	271	244	203	174	152	135	122	97	
	EC	5,52	80	552	2,17	651	521	434	372	325	289	260	217	186	163	145	130	104	
	VC	6,21	90	621	2,30	690	552	460	394	345	307	276	230	197	173	153	138	110	
	VC	6,89	100	690	2,43	728	582	485	416	364	323	291	243	208	182	162	146	116	
MESH 50	VC	7,58	110	758	2,54	763	611	509	436	382	339	305	254	218	191	170	153	122	
MJ195/3 PB-IA 05	UC	2,07	30	207	1,66	498	399	332	285	249	221	199	166	142	125	111	100	80	
	UC	2,76	40	276	1,92	575	460	384	329	288	256	230	192	164	144	128	115	92	
	EC	3,45	50	345	2,14	643	515	429	368	322	286	257	214	184	161	143	129	103	
	EC	4,14	60	414	2,35	705	564	470	403	352	313	282	235	201	176	157	141	113	
	EC	4,83	70	483	2,54	761	609	507	435	381	338	304	254	217	190	169	152	122	
	VC	5,52	80	552	2,71	814	651	542	465	407	362	325	271	232	203	181	163	130	
	VC	6,21	90	621	2,88	863	690	575	493	431	384	345	288	247	216	192	173	138	
	VC	6,89	100	690	3,03	910	728	606	520	455	404	364	303	260	227	202	182	146	
MESH 50	VC	7,58	110	758	3,18	954	763	636	545	477	424	382	318	273	239	212	191	153	
MJ195/4 PB-IA 06	UC	2,07	30	207	1,99	598	478	399	342	299	266	239	199	171	149	133	120	96	
	UC	2,76	40	276	2,30	690	552	460	394	345	307	276	230	197	173	153	138	110	
	EC	3,45	50	345	2,57	772	617	515	441	386	343	309	257	221	193	172	154	123	
	EC	4,14	60	414	2,82	846	676	564	483	423	376	338	282	242	211	188	169	135	
	EC	4,83	70	483	3,04	913	731	609	522	457	406	365	304	261	228	203	183	146	
	EC	5,52	80	552	3,25	976	781	651	558	488	434	391	325	279	244	217	195	156	
	VC	6,21	90	621	3,45	1.036	828	698	592	518	460	414	345	296	259	230	207	166	
	VC	6,89	100	690	3,64	1.092	873	728	624	546	485	437	364	312	273	243	218	175	
MESH 50	VC	7,58	110	758	3,82	1.145	916	763	654	572	509	458	382	327	286	254	229	185	