




FOR 0,35M SPACING CONSULT PAGE 137



PRODUCES DROPLETS
**VERY FINE
TO FINE**
ACCORDING TO WORKING PRESSURE

OPENING ANGLE



60°

FLAT FAN



15 - 60 PSI
1,03 - 4,14 bar
103 - 414 kPa

- High durability ceramic nozzle (99% alumina) with outstanding wear-resistance.
- Excellent flow rate precision (ISO 10625:2018).
- Produces 60° offset flat fan spray pattern.
- The ceramic orifice ensures good standardization and droplet distribution on the target.
- Good for directed spraying.
- Used at the end of the spray boom around the perimeter of the field to protect sensitive crops.

FOR MORE
INFORMATION

CAP
pg 54PACK WITH
10 unSTRAINERS
pg 83

CODE NOZZLE	DROPS SIZE	BAR	PSI	kPa	L/min	LITERS PER HECTARE													
						4	5	6	7	8	9	10	12	14	16	18	20	25	
						km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h	km/h
MJ192 PB 01	M	1,03	15	103	0,23	70	56	47	40	35	31	28	23	20	18	16	14	11	
	F	1,38	20	138	0,27	81	65	54	46	41	36	33	27	23	20	18	16	13	
	F	2,07	30	207	0,33	100	80	66	57	50	44	40	33	28	25	22	20	16	
	F	2,76	40	276	0,38	115	92	77	66	58	51	46	38	33	29	26	23	18	
	F	3,45	50	345	0,43	129	103	86	74	64	57	51	43	37	32	29	26	21	
MESH 100	F	4,14	60	414	0,47	141	113	94	81	70	63	56	47	40	35	31	28	23	
MJ193 PB 015	M	1,03	15	103	0,23	70	56	47	40	35	31	28	23	20	18	16	14	11	
	M	1,38	20	138	0,27	81	65	54	46	41	36	33	27	23	20	18	16	13	
	F	2,07	30	207	0,50	149	120	100	85	75	66	60	50	43	37	33	30	24	
	F	2,76	40	276	0,58	173	138	115	99	86	77	69	58	49	43	38	35	28	
	F	3,45	50	345	0,64	193	154	129	110	96	86	77	64	55	48	43	39	31	
MESH 100	F	4,14	60	414	0,70	211	169	141	121	106	94	85	70	60	53	47	42	34	
MJ194 PB 02	M	1,03	15	103	0,35	106	85	70	60	53	47	42	35	30	26	23	21	17	
	M	1,38	20	138	0,41	122	98	81	70	61	54	49	41	35	31	27	24	20	
	M	2,07	30	207	0,66	199	159	133	114	100	89	80	66	57	50	44	40	32	
	F	2,76	40	276	0,77	230	184	153	131	115	102	92	77	66	58	51	46	37	
	F	3,45	50	345	0,86	257	206	172	147	129	114	103	86	74	64	57	51	41	
MESH 50	F	4,14	60	414	0,94	282	225	188	161	141	125	113	94	81	70	63	56	45	
MJ195 PB 03	M	1,03	15	103	0,47	141	113	94	81	70	63	56	47	40	35	31	28	23	
	M	1,38	20	138	0,54	163	130	108	93	81	72	65	54	46	41	36	33	26	
	M	2,07	30	207	1,00	299	239	199	171	149	133	120	100	85	75	66	60	48	
	F	2,76	40	276	1,15	345	276	230	197	173	153	138	115	99	86	77	69	55	
	F	3,45	50	345	1,29	386	309	257	221	193	172	154	129	110	96	86	77	62	
MESH 50	F	4,14	60	414	1,41	423	338	282	242	211	188	169	141	121	106	94	85	68	
MJ196 PB 04	M	1,03	15	103	0,94	282	225	188	161	141	125	113	94	81	70	63	56	45	
	M	1,38	20	138	1,08	325	260	217	186	163	145	130	108	93	81	72	65	52	
	M	2,07	30	207	1,33	399	319	266	228	199	177	159	133	114	100	89	80	64	
	M	2,76	40	276	1,53	460	368	307	263	230	205	184	153	131	115	102	92	74	
	M	3,45	50	345	1,72	515	412	343	294	257	229	206	172	147	129	114	103	82	
MESH 50	M	4,14	60	414	1,88	564	451	376	322	282	251	225	188	161	141	125	113	90	
MJ196/1 PB 05	C	1,03	15	103	0,94	282	225	188	161	141	125	113	94	81	70	63	56	45	
	C	1,38	20	138	1,08	325	260	217	186	163	145	130	108	93	81	72	65	52	
	C	2,07	30	207	1,66	498	399	332	285	249	221	199	166	142	125	111	100	80	
	M	2,76	40	276	1,92	575	460	384	329	288	256	230	192	164	144	128	115	92	
	M	3,45	50	345	2,14	643	515	429	368	322	286	257	214	184	161	143	129	103	
MESH 50	M	4,14	60	414	2,35	705	564	470	403	352	313	282	235	201	176	157	141	113	
MJ196/2 PB 06	VC	1,03	15	103	1,17	352	282	235	201	176	157	141	117	101	88	78	70	56	
	VC	1,38	20	138	1,36	407	325	271	232	203	181	163	136	116	102	90	81	65	
	VC	2,07	30	207	1,99	598	478	399	342	299	266	239	199	171	149	133	120	96	
	C	2,76	40	276	2,30	690	552	460	394	345	307	276	230	197	173	153	138	110	
	C	3,45	50	345	2,57	772	617	515	441	386	343	309	257	221	193	172	154	123	
MESH 50	M	4,14	60	414	2,82	846	676	564	483	423	376	338	282	242	211	188	169	135	