



PRODUCES DROPLETS

VERY FINE

ACCORDING TO WORKING PRESSURE

OPENING ANGLE



85°

HOLLOW CONE



80 - 150 PSI
5,52 - 10,34 bar
552 - 1034 kPa

- High durability ceramic nozzle (99% alumina) with outstanding wear-resistance.
- Produces 85° hollow cone spray pattern.
- The ceramic orifice ensures good standardization and droplet distribution on the target.
- It is indicated for insects, fungi, mites and bacteria control with systemic products and contact in enclosed environments.
- Recommended for misting systems.

FOR MORE
INFORMATION



CAP
Pg 54



PACK WITH
10 un



STRAINERS
Pg 83

CODE	NOZZLE	PRESSURE							
		80 lbf/pol ²	90 lbf/pol ²	100 lbf/pol ²	110 lbf/pol ²	120 lbf/pol ²	130 lbf/pol ²	140 lbf/pol ²	150 lbf/pol ²
MJ074	SERIE-X 0,50	0,058	0,062	0,065	0,068	0,071	0,074	0,077	0,080
MJ075	SERIE-X 1	0,125	0,135	0,140	0,147	0,153	0,160	0,166	0,171
MJ076	SERIE-X 2	0,170	0,180	0,190	0,199	0,208	0,217	0,225	0,233
MJ077	SERIE-X 3	0,259	0,275	0,290	0,304	0,318	0,331	0,343	0,355

LITERS PER MINUTE